

Smart Interactive Display

MW3565-U-E



Key Features

- 4K UHD anti-glare display delivers images with extreme detail.
- Zero bonding technology between lcd panel and cover glass brings brighter viewing and smoother touching experience.
- Ultra-narrow and equal-width bezel design for perfect aesthetics.
- Minimalist geometric line design and smooth border outline, elegant and attractive.
- 8MP professional HD camera for more immersive remote collaboration.
- Omni-directional 8-array microphone, 8m pickup distance, zero communication distance.
- Dual Wi-Fi modules with both Wi-Fi and hotspot support.
- Dual-channel, 6-array speaker brings high-quality surround sound.
- High-precision infrared touch technology allows up to 20-point touch, realizing smooth co-authoring.
- Bluetooth 5.2 offers higher data transmission rate, and lower power consumption.
- 4K UI, mobile-level operation, just like use a mobile phone.
- A variety of quick tools, such as annotation, screenshot, etc., improve usability and interaction efficiency.
- Wireless screen mirroring from various operating systems such as Android, iOS and Windows to the display with one touch.
- Fast file transfer. Allows users to quickly transfer files to the display via a QR code.
- OTA remote upgrade. The system can be upgraded online without backing up data.



Specifications

Smart interactive display

Model	MW3565-U-E	
Panel		
Backlight	DLED	
Panel size	65 inches	
Resolution	3840*2160	
Brightness (cd/m²)	350	
Contrast ratio	1200:1	
Response time (ms)	8	
Color support	1.07B	
Viewing angle (H/V)	178°/178°	
Android		
CPU	RK3588: 4-core A76 (2.4G) + 4-core A55 (1.8G)	
CPU frequency	2.4GHz	
RAM/ROM	DDR4: 8GB eMMC: 64GB	
Android version	Android 12.0	
Touch		
Touch control	Infrared touch screen, 20-point multi-touch at most	
Touch precision (mm)	±1	
Recognizable object	5 points 2mm	
Glass	4mm tempered glass, level 7 on Mohs hardness scale, anti-glare	
Response time (ms)	≤10	
Touchscreen input	Opaque objects (e.g. finger, pen, etc.)	
Interface		
Video input	3*HDMI IN (4K@60)	
Video output	1*HDMI OUT (4K@60)	
Audio input	1*AUDIO IN	
Audio output	1*AUDIO OUT	
Control	1*RS232、3* USB 3.0、1* USB Type C、1* USB Type B	
Network	2*RJ 45,10M/100M/1000M adaptive Ethernet Interfaces	
Audio		



Frequency domain	80Hz~20kHz	
Speaker	Left channel 17W: 1*treble (8 Ω 5W) + 2*bass (4 Ω 6W)	
	Right channel 17W: 1*treble (8 Ω 5W) + 2*bass (4 Ω 6W)	
Wi-Fi		
Configuration	Wi-Fi6 + Wi-Fi5 dual-module, supports 5G/2.4G	
Performance	30 m ² coverage, 20m transmission distance in open space	
Bluetooth		
Version	5.2	
Performance	10m transmission distance in open space	
OSD		
Language supported	3 (Simplified Chinese、English、Spanish)	
VESA		
Wall mount hole (mm)	500*400	
Wall mount screw	4-M8 screw hole	
General		
Power supply	AC 100 to 240V, 50/60Hz	
Maximum power consumption (W)	≤220 (on without OPS)	
Standby power consumption (W)	<0.5	
Operating temperature	0 to 50°C	
Operating humidity	10% to 90% (non-condensing)	
Storage temperature	-20 to 60°C	
Storage humidity	0% to 95% (non-condensing)	
Product dimensions (W*H*D)(mm)	1498*911*89	
Package dimensions (W*H*D)(mm)	1632*1081*222	
Weight (kg)	Net weight: 40.5	
	Gross weight:49.0	
Accessories included	1*power cord、2*touch pen、1*quick guide	

Pluggable 4K Camera Microphone Module

Model	HB-7199-CA08
General	
Camera resolution	4K@30fps
Sensor pixel size (um)	1.45*1.45
FOV	Diagonal 112.7°



Distortion	≤2%
Microphone	Omni-directional 8-array
Pickup angle	180°
Pickup distance (m)	8
Pickup capability	Supports echo cancellation, auto gain, and noise suppression
Product dimensions (W*H*D)(mm)	359*50*46


Pluggable MIC Module

Model	HB-7199-MC04	
General		
Specification	Omni-directional 4-array	
Pickup angle	180°	
Pickup distance (m)	8	
Pickup capability	Supports echo cancellation, auto gain, and noise suppression	
Product dimensions (W*H*D)(mm)	200*50*38	


Appearance

Dimensions


Smart interactive display:








Pluggable 4K Camera Microphone Module:



Pluggable MIC Module:






Interfaces

Front interfaces



Side interfaces



Example of module installation

Pluggable 4K Camera Microphone Module:



Pluggable MIC Module:





Order Information

Model	Remarks
MW3565-U-E	65" Smart interactive display
HB-7199-CA08	Pluggable 4K Camera Microphone Module (optional)
HB-7199-MC04	Pluggable MIC Module (optional)
HB-7199-TP	Wireless screen sharing dongle (optional)
HB-4365	65" to 86" Wall mount (optional)
HB-8765-S	65" to 86" Mobile stand (optional)
HB-7099-M1	Pluggable PC module with i5 processor (Windows 10, not activated) (optional)
HB-7099-S1	Pluggable PC module with i7 processor (Windows 10, not activated) (optional)
LIS-WIN10-V	OS-Windows 10-1 to 1 license-IoT Enterprise Value version (with i5 processor OPS PC module) (optional)
LIS-WIN10-H	OS-Windows 10-1 to 1 license-IoT Enterprise High End version (with i7 processor OPS PC module) (optional)

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseas business@uniview.com; global support@uniview.com

http://www.uniview.com

©2023 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

^{*}Product specifications and availability are subject to change without notice.